- (h) Each holder of a Parts Manufacturer Approval shall establish and maintain a fabrication inspection system that ensures that each completed part conforms to its design data and is safe for installation on applicable type certificated products. The system shall include the following:
- (1) Incoming materials used in the finished part must be as specified in the design data.
- (2) Incoming materials must be properly identified if their physical and chemical properties cannot otherwise be readily and accurately determined.
- (3) Materials subject to damage and deterioration must be suitably stored and adequately protected.
- (4) Processes affecting the quality and safety of the finished product must be accomplished in accordance with acceptable specifications.
- (5) Parts in process must be inspected for conformity with the design data at points in production where accurate determination can be made. Statistical quality control procedures may be employed where it is shown that a satisfactory level of quality will be maintained for the particular part involved.
- (6) Current design drawings must be readily available to manufacturing and inspection personnel, and used when necessary.
- (7) Major changes to the basic design must be adequately controlled and approved before being incorporated in the finished part.
- (8) Rejected materials and components must be segregated and identified in such a manner as to preclude their use in the finished part.
- (9) Inspection records must be maintained, identified with the completed part, where practicable, and retained in the manufacturer's file for a period of at least 2 years after the part has been completed.
- (i) A Parts Manufacturer Approval issued under this section is not transferable and is effective until surrendered or withdrawn or otherwise terminated by the Administrator.
- (j) The holder of a Parts Manufacturer Approval shall notify the FAA in writing within 10 days from the date the manufacturing facility at which the parts are manufactured is relocated

- or expanded to include additional facilities at other locations.
- (k) Each holder of a Parts Manufacturer Approval shall determine that each completed part conforms to the design data and is safe for installation on type certificated products.

[Amdt. 21–38, 37 FR 10659, May 26, 1972, as amended by Amdt. 21–41, 39 FR 41965, Dec. 4, 1974; Amdt. 21–67, 54 FR 39291, Sept. 25, 1989]

§ 21.305 Approval of materials, parts, processes, and appliances.

Whenever a material, part, process, or appliance is required to be approved under this chapter, it may be approved—

- (a) Under a Parts Manufacturer Approval issued under §21.303;
- (b) Under a Technical Standard Order issued by the Administrator. Advisory Circular 20–110 contains a list of Technical Standard Orders that may be used to obtain approval. Copies of the Advisory Circular may be obtained from the U.S. Department of Transportation, Publication Section (M–443.1), Washington, D.C. 20590;
- (c) In conjunction with type certification procedures for a product; or
- (d) In any other manner approved by the Administrator.

[Amdt. 21–38, 37 FR 10659, May 26, 1972, as amended by Amdt. 21–50, 45 FR 38346, June 9, 1990]

Subpart L—Export Airworthiness Approvals

SOURCE: Amdt. 21–2, 30 FR 8465, July 2, 1965, unless otherwise noted.

§21.321 Applicability.

- (a) This subpart prescribes—
- (1) Procedural requirements for the issue of export airworthiness approvals; and
- (2) Rules governing the holders of those approvals.
 - (b) For the purposes of this subpart—
- (1) A Class I product is a complete aircraft, aircraft engine, or propeller, which—
- (i) Has been type certificated in accordance with the applicable Federal Aviation Regulations and for which Federal Aviation Specifications or type